



1-way cassette



Features

- Capacity range: 300CFM to 400CFM.
- Smoother air flow with less turbulence.
- One direction air flow guarantees quick cooling, flexible installation position.
- Space saving, only 235mm in height.
- Built-in drain water pump with 750mm pumping head.
- Four-speed motor with one reserved for more choice .
- Fresh air provision makes life healthier and more comfortable.



Specifications

Model MKC-			300R(A)	400R(A)
Air Volume	High	m ³ /h	500	630
		CFM	300	370
	Med	m ³ /h	450	560
		CFM	270	330
	Low	m ³ /h	400	500
		CFM	240	300
Cooling Capacity		W	3,040	3,790
Heating Capacity		W	5,130	6,410
Electrical Auxiliary Heater (EAH)		W	1,000	1,000
Power Input		W	60	60
Noise(Hi/Med/Lo)		dB(A)	38/35/33	40/37/35
Water Flow		l/min	8.7	10.9
Water Pressure Drop		kPa	10.1	14.5
Fan Motor	Type	Low noise 4-speed fan motor		
Fan	Type	Centrifugal, forward-curved Blades		
Coil	Row	3		
	Working Pressure	MPa	1.6	
Panel	Net Dimension (W×H×D)	mm	1,050×18×470	
	Net Weight	kg	4	
Indoor Unit	Net Dimension (W×H×D)	mm	850×235×400	
	Net Weight (with EAH)	kg	22.5(23)	
Pipe Connection	Water-inlet pipe	Inch	RC3/4"	
	Water-outlet pipe	Inch	RC3/4"	
	Drain pipe	mm	ODØ18	

Note:

1. The data is the performance in high speed.
2. Cooling Conditions: Entering Water 7°C, Temperature Rise 5°C, Entering Air Temperature 27°CDB,19°CWB.
Heating Conditions: Entering Water 50°C, enter air temperature 20°C, the same water flow as the cooling conditions.
3. Noise level is tested in full-anechoic room.
4. The EAH capacity only available with A type unit.